

Technical specifications

Chassis

- Outside length 910 mm
- Outside width incl. foot pedal 600 mm
- Outside width incl. arm rests 845 mm
- White paint finish
- 2 pcs. double castors \varnothing 100 mm
- 2 pcs. rigid castors \varnothing 35 mm
- Optional: foot keypad (2 memory positions, M1/M2)

Upper frame

- 4-part support frame (head, back, seat, leg part)
 - Length 1,950–2,230 mm
 - Width of upholstery 600 mm
 - Entry height 550 mm
 - Removeable upholstery
- | | Angle | Dimensions (L x W) |
|---------------------|--------------------|--------------------|
| • Head part | -27/+180° | 280 x 420 mm |
| • Back part | -23/+85° | 710 x 600 mm |
| • Seat part | -3/+28° | 510 x 600 mm |
| • Leg part | 0/-75° | 490 x 530 mm |
| • Height adjustment | | 615–890 mm |
| • Armrests | 0/+180° | 455 x 75 mm |
| • Legroom surgeon | | 485–760 mm |
| • CPR/flatposition | (height back part) | 600 mm |

Electrical control

- All components according to IP54
- Hand control with 8 individually programmable memory positions, auto run function, reset button
- Foot keypad (optional)

Electric Drives

- Back, seat, leg part, total up/down

Lifting column

- Max. lifting 275 mm
- Max. load 240 kg
- Motors IPX4 with HAL sensors, to be memorized

Seat part/CPR



Back part/leg part



Height adjustment/legroom



Application example

assistTrend
+ armrest pair

Item No.: 2500 0002
+ Item No.: 3300

500 ECO

Item No.: 1500 0008



Further technical details

- Chair has detachable, swiveling armrests made completely with PUR foam
- Detachable seat for service friendly access to electric components

Max.. load 240 kg

Weight 90 kg

Subject to technical modifications.

Equipment protection

Paper rolls *stay Clean roll*

White embossed, 2-ply, 50 cm x 50 m
Carton á 9 pieces **Item No.:** 3034 0021

Page 67



Upholstery/color card

Standard color

anthracite (main color)
+ chrome (accent color)
Item No.: 3037 0092

“Tundra skai”
Page 102

“Pandoria Plus”
Page 103

